



How to Design and Implement a Dam Removal

Brian Graber
American Rivers

Illinois Dam Removal Project Management Training
March 11, 2014

Before/After Project Examples



Billington Street Dam Town Brook, Plymouth, MA



Before



During (fall 2002)

Billington Street Dam Town Brook, Plymouth, MA



After (2011)



Two other Town Brook dams block 95% of fish even with fish ladders





Merrimack Village Dam
Souhegan River
Merrimack, NH



Merrimack Village Dam former impoundment immediately after removal





Black Brook Manchester, NH

Weeks after removal





Woolen Mills Dam Milwaukee River West Bend, WI

One week after
removal
Winter 1988





Riverside Park
Milwaukee River, West Bend, WI






Cotton Mill Dam
Satucket River
August 11, 2001

Satucket River
October 3, 2001





Goals:

- 1) Understand the dam removal process
- 2) Be able to scope out the components of a project



Dam Components






Dam removal science/design includes 6 components



Data
Collection/
Surveying



Hydrology/
Hydraulics



Sediment
Management



Protecting
Infrastructure



Species
Protection



Site-Specific
Issues



Consider long-term benefits vs. short-term impacts



Flow Regime



Water Quality



Continuity



Complexity

Design Components: Long-Term Benefits/Short-Term Impacts

Some *short-term* impacts occur during construction



Sediment movement



Construction access



Habitat change



There are 3 potential long-term impacts if not managed well



Contaminants



T & E species



Infrastructure



Data Collection and Surveying



Data
Collection/
Surveying





Find existing data on the dam and the river

Past Dam Inspections (state dam safety)

FEMA - FIS, profiles, plans, and computer model (state, town library or engineer), or

<http://www.msc.fema.gov>

Aerial or orthophotographs (web or order)

<http://maps.google.com>

<http://earth.google.com>

USGS topographic mapping

Local topographic mapping (town, state, web)

Sanborn mapping (commercial properties to 1867):

<http://www.edrnet.com/sanborn.htm>

Historic topo maps: <http://historical.maptech.com>

For northeast:

<http://docs.unh.edu/nhtopos/nhtopos.htm>

Tax Assessors Mapping (town)

Geological mapping

GIS Data (town, region, or state)

State Rare & Endangered Species Mapping

Wetland Mapping

EPA Watershed Mapping & Info

<http://www.epa.gov/surf/>

USGS Gauge Data (flow & sediment)

<http://water.usgs.gov/>

Additional Flow Data (state, web, ACOE, local group, old reports)

Fisheries Data (state)

Past Plans (of dam, site, or nearby construction)

(DOT, town engineer, state)

Permit applications (town, state, feds, or web)

Old Reports (environmental, historic, engineering, planning, state studies, etc.)

Photographs (current and historic) (town, neighbors)


Historic Records (town, state)

FERC Reports: <http://elibrary.ferc.gov>

Utility Information (town or state)

Web pages for local recreation

Survey dam structure, longitudinal profile, cross sections, and sediment depths



Sediment depth can be measured with a sediment probe or a metal rod




Design Components: Data Collection


Be careful to survey through extent of original impoundment



Design Components: Data Collection/Surveying





TIME






Rindge Dam
Malibu Creek, CA





Design Components: Data Collection/Surveying

Hydrology/Hydraulics



What's the difference between hydrology and hydraulics?

Hydrology:

Magnitudes and probabilities of flows

Hydraulics:



Depths and velocities of flows




Does your dam provide
flood control?
Probably not

↓
No Flood Storage Potential:
has full impoundment and
constant flow over spillway

Flood Storage Potential:
has storage volume and flow
through a controlled outlet



What's a HEC-RAS and when do you need one?



- Infrastructure protection
- To prove fish passage
- Post-project water levels for stakeholders
- Advanced sediment transport modeling
- To address flood control?

Sediment Management



Sediment
Management

General Concepts in Dam Removal Sediment Management





Rivers naturally carry sediment



Sediment can be harmful or beneficial



General Sediment Concepts: Grain Sizes

Coarse grain sediment can be beneficial to habitat

Fine grain sediment release (clay and silt)

- Can clog habitat downstream
- Can have direct impacts on species respiration

Coarse grain (cobble and gravel)

- Forms the basis of habitat for many species

Not all dams have a lot of sediment




General Sediment Concepts: Quantity Variability

Not all sediment moves



General Sediment Concepts: Sediment Mobility

As impoundment width increases, percent sediment release decreases




From: Sawaske, S.R. and Freyberg, D.L. 2012. A comparison of past small dam removals in highly sediment-impacted systems in the U.S. *Geomorphology* 151-152: 50-58.

Assess the quantity, particle sizes, quality, and potential mobility of impounded sediment



The longitudinal profile is a fundamental sediment analysis tool




Test sediment for contaminants and compare to ecological and human risk thresholds




- Complete 'due diligence'
- Assess quantity of sediment
- Collect sediment cores (not grabs)
- Test for organics and heavy metals
- Compare test concentrations to human risk and ecological thresholds

National Subcommittee on Sedimentation Protocols



Reservoir Sediment Volume (V_s) Relative to the Average Annual Sediment Load (Q_s)



Scale analysis and management to sediment volume



NH Barrier Removal Sediment Assessment & Management Protocol Flow Chart

Assumptions:

- **Anthropogenic** barrier removal is beneficial to river health.
- The total volume of potentially mobile impounded sediment is critical to the sediment management process. As such, the level of sediment contaminant testing should be commensurate with the volume of potentially mobile impounded sediment.
- Projects with small amounts of potentially mobile impounded sediment and **no or limited** due diligence issues should be able to proceed with no contaminant testing.
- Sediment assessment and management protocols should not always be determined on a case-by-case basis. A standardized sediment assessment and management protocol should be utilized until specific sediment volume or contamination thresholds are exceeded.
- Natural erosion of the potentially mobile impounded sediment should be the preferred sediment management alternative unless conditions/factors dictate otherwise.

#8
No contaminant testing or sediment management required

#1
Conduct due diligence review

#2
Determine quantity of impounded sediment

#3
Determine potential mobility of impounded sediment

#4
Conduct characterization of potentially mobile sediment

#5
Assess whether mobile portion of sediment is likely to **"cause problems"** downstream or upstream

#6
Does due diligence review suggest contaminant or other issues?

#7
Is mobile portion of impounded sediment likely to **"cause problems"** downstream or upstream?

Yes

Yes

No

No

Yes

There are several approaches to managing clean sediment (depending on quantity and particle sizes)



- Natural erosion
- Sediment removal (dredging)
- Stabilize in place
 - Open dam gates
 - Remove dam slowly
 - Remove dam in stages
- Combined approaches

Photo: John Gussman

There are fewer approaches to managing contaminated sediment

- Management options
 - Remove and dispose
 - Isolate and cap
- If contaminant management is necessary, can greatly add to cost of project
- Conundrum: dams are not good hazardous waste containment facilities

Merrimack Village Dam Souhegan River, NH



Design Components: Natural Erosion

Dufresne Dam, Battenkill, VT



Design Components: Stabilize Sediment

Protecting Infrastructure



Protecting
Infrastructure

Look in and along impoundment and in the dam for at-risk bridges, retaining walls, or utilities



Design Components: Protecting Infrastructure

Assess whether any infrastructure is at risk



Bridges



Retaining walls



Utilities

Consider if infrastructure can be moved first;
next consider direct stabilization



Bridges



Retaining
walls



Utilities

Species Protection



Identify if species of concern could be affected by dam removal

- Contact Illinois Natural Heritage Program for species of concern database search



- Species information by county is available online

Manage for Aquatic Species





Revegetate and consider multiple species and multiple life stages in additional restoration plans



Design Components: Species Protection



The majority of the habitat restoration comes from removing the dam

Water quality, flow regime, connectivity, complexity

- Restored fish passage
- Restored connectivity along bed, banks, riparian area
- Temperature regime improvement (and associated dissolved oxygen)
- Restored riverine flow characteristics
- Restored sediment dynamics
- Cleaned substrate
- Restored vegetative cover long-term
- Restored riverine bed features long-term

Dam removal sets river on a trajectory to restore long-term habitat if given freedom to do its own work



Habitat Formation

Is the river free to create habitat?

- Urban settings
- Give the river as much space as possible



Stream Power:

Baseflow dominated spring creeks take longer to form habitat than powerful rivers



Woody habitat provides:

- Habitat cover
- Bed complexity
 - Creates and maintains pools
- Habitat stability:
Decreased erosive power
 - wood only 2% of streambed area, but accounted for 50% of the total flow resistance (Manga and Kirchner 2000)
- Better species response than other active habitat additions



Site-Specific Issues



Site-Specific
Issues



Dam uses can often
be replaced



Design Components: Site-Specific Issues

Other site-specific issues:


well impacts, parks, walking trails,
renderings, etc.



You now have the basis for writing a scope of work



Data
Collection/
Surveying



Hydrology/
Hydraulics



Sediment
Management



Protecting
Infrastructure



Species
Protection



Site-Specific
Issues

There are several approaches to removing a structure



Explosives



Heavy Machinery



By Hand

Explosives are rarely used in most parts of the country



Dam blasting set for Wednesday to sound like boom of 20 cannons

By TIM CHITWOOD — tchitwood@ledger-enquirer.com

Posted: 12:06am on Mar 18, 2012; Modified: 5:50pm on Mar 20, 2012

 Like  6 people like this. Be the first of your friends.



Eagle & Phenix Dam
Chattahoochee River,
Georgia

Tim Chitwood: Crank that dam blast up to a crowd pleaser

By Tim Chitwood — tchitwood@ledger-enquirer.com

For gosh sakes will someone please blow something up here in a way folks can appreciate?

"My dog didn't even jump," said a woman hugging a wee pup Wednesday when a portion of the Eagle & Phenix dam was dynamited, and so many dreams of devastation were deferred.

"Is that it?" asked another bystander.

"I can't believe that's all it was," said a third.

It was a dam shame that so dam many were drawn downtown by a dam explosion that was so dam disappointing.

The dam blew up precisely as planned, and that totally ticked everyone off. No one got hurt, no windows broke, and no shattered rock rained upon witnesses, not even people partying in luxury lofts within the old Eagle & Phenix mill that once ran on dam power.

In fact the blast was so well contained that some could hardly hear it. Critics compared it to the flatulence of small animals, favoring fish for brevity and alliteration. The wind broken by digesting popcorn also was mentioned.

This is what happens when you let professionals handle dynamite: They so well calculate the explosive force needed, and so well cover the blast site with fabric and metal fence, that no rock or other debris goes airborne to plummet upon cars, buildings or passersby.

Leave that work to volunteers and you wouldn't have that problem.

Construction Approaches

First, slowly drain the impoundment



Most commonly a backhoe with a hydraulic hammer will breach one side and then move across





We have also used more careful construction approaches



Near-site disposal of material saves money and is often preferred by regulators



(De)construction approaches usually work “in the wet”





Massachusetts: Billington Street Dam Removal, Town Brook



Massachusetts: Ox Pasture Brook Dam Removal, Ox Pasture Brook



Connecticut: Union City Dam Removal, Naugatuck River



New Hampshire: Merrimack Village Dam Removal, Souhegan River



North Carolina: Dynamo Dam Removal, Little River

A scenic view of a wooden bridge spanning a river. The bridge has a wooden deck and a metal truss structure. The river is calm, and the banks are rocky and covered with green vegetation. A person is visible on the rocky bank near the water's edge.

Things that Go Wrong

(And How to Make
Them Go Right)



Along with experience, look for non-technical skills and integration of skills

Important non-technical skills:

- Responsiveness and project management
- Permitting
- Presentation skills
- Willingness to advocate for resource and project

No one firm is truly good
at all of these

Integration of technical skills:

- Engineering
- Geomorphology
- Ecology

Traditional engineers may miss river context and habitat



Hiring Consultants: Skill Integration

Blend geomorphology, ecology, and engineering skills:




Remove the full vertical extent of the dam (and as much of the lateral extent as possible)




Construction oversight is critical



Be cautious/skeptical with structural approaches





Active habitat additions (cross vanes, weirs, lunkers, etc.) need to be used appropriately

- High failure risk
 - 40-70% failure rate shown in studies
 - higher in volatile environment of drained impoundment
- Can take river out of context (forcing different structure on river)
- May not actually help habitat long-term (according to several studies)



Decision-Making Process for Applied Habitat Management

- 1) What will happen if we do nothing besides remove the dam?
 - consider 50-100 year timeframe
- 2) Assess whether river has the power and material to build habitat once freed
- 3) Simulate nature if actively managing

Dam Removal Clearinghouse:

<http://wrca.library.ucr.edu/CDRI/>

Brian Graber
American Rivers
bgraber@americanrivers.org



American Rivers
Rivers Connect Us