
Monitoring of Downstream Salmon and Steelhead Trout at Federal Hydroelectric Facilities

U.S. Department of Energy Bonneville Power Administration Division of Fish & Wildlife

National Oceanic and Atmospheric Administration National Marine Fisheries Service Environmental & Technical Services Division

November 1985



This report was funded by the Bonneville Power Administration (BPA), U.S. Department of Energy, as part of BPA's program to protect, mitigate, and enhance fish and wildlife affected by the development and operation of hydroelectric facilities on the Columbia River and its tributaries. The views in this report are the author's and do not necessarily represent the views of BPA.

For copies of this report, write:

Bonneville Power Administration Division of Fish and Wildlife Public Information Officer - PJ P.O. Box 3621 Portland, OR 97208



MONITORING OF DOWNSTREAM SALMON AND STEELHEAD AT FEDERAL HYDROELECTRIC FACILITIES - 1985



by Richard C. Johnsen and Carol L. Ranck

Annual Report of Project 84-14 financed by Bonneville Power Administration (Agreement DE-AI79-85BP20733)

Environmental and Technical Services Division Northwest Region National Marine Fisheries Service National Oceanic and Atmospheric Administration 847 N.E. 19th Avenue Portland, Oregon 97232

November 1985

and

TABLE OF CONTENTS

NTRODUCTION	
ETHODS AND MATERIALS	2
ESULTS AND DISCUSSION	4

SUMMARY	
RECOMMENDATIONS	
ACKNOWLEDGEMENTS	
LITERATURE CITED	
APPENDIX A	



INTRODUCTION

Juvenile salmonids were monitored on their seaward migration at three key sites on the Snake-Columbia River system by the National Marine Fisheries Service (NMFS). This was a part of the total monitoring effort in the Water Budget Center's (WBC) smolt monitoring program on Columbia Basin salmonid stocks. In addition to the three key sites, the NMFS also initiated a sampling effort at Lower Monumental Dam. Funding was provided by the Bonneville Power Administration (BPA).

The major sampling sites were at Lower Granite, McNary, and John Day Dams: sampling at these sites provided data primarily for evaluation of smolt survival, travel time, and migrational timing as required by the WBC. At Lower Monumental Dam catch data was to provide a general indication of smolt passage and comparison with the hydroacoustics passage index as determined by Bio-Sonics of Seattle, WA. To achieve these goals it was necessary to monitor and index salmonid smolt passage at the three major sites. This involved: 1) the systematic sampling of the smolt migration from 27 March to 23 July at Lower Granite Dam, 29 March to 26 September at McNary Dam, 28 March to 1 April, 20-22 April, and 27 April to 29 October at John Day Dam; 2) recovering and recording brands; 3) providing the WBC with a daily index of smolt passage at Lower Granite and McNary Dams and daily sample numbers at John Day Dam; and 4) providing the WBC with daily summaries of brand recapture data. Daily catch and brand recapture data from Lower Monumental Dam was reported to the WBC as required during the sampling season, 23 May through 9 July.

METHODS AND MATERIALS

As in 1984 (Johnsen, et. al., 1984), monitoring the smolt migration at Lower Granite and McNary Dams was by sampling, by time, a portion of the total number of smolts from the gatewell collection system. The target rate was the lesser of 3% of the estimated weekly outmigration or 10% of the weekly total of smolts collected or bypassed (FTOT Annual Work Plan, 1985). At John Day Dam initially (28 March to 1 April), sampling was identical to 1984 using the airlift pump system in Unit 3, gatewells B and C; this was prior to installation and testing of the submerged traveling screens (STS). Sampling at John Day Dam after 20 April was with the STS installed; samples from 20-22 April were from dipnetting Unit 3, and from 27 April to the end of the season were from the airlift pump system in gatewell B of Unit 3. Samples at Lower Monumental Dam were obtained with a specially constructed gatewell dipnet fished in the bulkhead gate slot. Sample numbers were relative because gatewell cleanout was not possible - a stored operating gate prevented dipnetting the total gatewell area

available to fish. Gatewells A, B, and C of Unit 2 were dipnetted until the unit went out of service on 16 June; gatewells A, B and C of Unit 3 were fished thereafter.

The sampling schedule at each site was typically as follows:

Site

Frequency

Lower Granite Dam

McNary Dam

John Day Dam

Lower Monumental Dam

Daily: 24-hour cumulative sample

Daily: 24-hour cumulative sample

Daily: 24-hourly samples

5 days per week: 8 hours per day

Reporting of data was daily or as requested by the WBC. To efficiently accomplish this, an IBM-PC transmission system (via phone line), was established by the WBC at the three main sites. Data from Lower Monumental Dam was reported weekly from the Rufus Field Station. Confirmation of data transmitted was for the most part an on-going joint effort between personnel from the sample site and the WBC as the season progressed. To take advantage of all possible brand recapture data, some follow-up verification was necessary by the NMFS staff to categorize reportings of partial or faded brands. This may at times be vital for statistical validation of certain mark groups by increasing the number of usable recoveries.

Analysis and evaluation of these monitoring data are being performed by the WBC. Detailed data from each sample site will be available in their 1985 smolt monitoring activities report.

RESULTS AND DISCUSSION

A summary of sampling results are presented in Table 1. In addition to the numbers of fish by species sampled at each site are the total numbers of branded fish captured, estimated numbers collected, and the number of days each species appeared in the sample. Figure 1 shows the portion of the season each species was found in the sample.

Sampling at Lower Granite and McNary was routine and essentially identical to 1984; no operational difficulties of significance were encountered.


Sampling at John Day Dam after installation of the STS in Unit 3 did, however, require a significant amount of operational testing, adjustment, and some minor modifications to the airlift pump components; this operational testing was necessary to compensate for the increased upwell flow in the gatewell and its effect on the fish. The search for a suitable funnel operating depth for hydraulic efficiency, while considering the well-being of the fish captured, required numerous changes in the sampling routine. A depth of about 20 feet, to the top of the funnel, was found to TABLE 1.--Summary of 1985 smolt sampling activities at Lower Granite, Lower Monumental, McNary, and John Day Dams.

TotalTotalNumber ofTotalnumberEstimated1/days speciesnumberof brandstotal numberoccurred in

Species	Dam	sampled	in sample	collected	sample
Yearling	Lower Granite	101,109	2,165	1,742,244	121
Chinook	Lower Monumental	5,187	32	5,187	31
	McNary	213,899	8,458	2,952,613	110
	John Day	63,578	1,960	63,578	108
Subyearling	Lower Granite	3,375	458	44,008	56
Chinook	Lower Monumental	3,116	0	3,116	22
	McNary	433,418	1,928	6,562,483	177
	John Day	226,577	80	226,577	179
Steelhead	Lower Granite	106,684	1,647	2,689,579	116
	Lower Monumental	8,347	3,918	8,347	32
	McNary	58,649	7,547	840,493	163
	John Day	36,616	2,113	36,616	150
Coho	Lower Granite	0	0	0	0
	Lower Monumental	0	0	0	0
	McNary	4,653	28	71,752	57
	John Day	600	3	600	51
Sockeye	Lower Granite	324	0	6,467	88
	Lower Monumental	4	0	4	3
	McNary	71,095	1,707	1,030,017	144
	John Day	17,235	334	17,235	98

1/ At John Day and Lower Monumental Dams the sample is the actual collection.





Lower

Monumental Chinook l

Chinook O

Steelhead

Coho

McNary


Sockeye


Sampling Ended September 26

Sampling Ended July 9

Chinook l

Chinook O





Mar 31 Apr 28 May 26 Jun 23 Jul 21 Aug 18 Sep 15 Oct 13 Figure 1.--Species represented during the 1985 smolt sampling season at Lower Granite, Lower Monumental, McNary, and John Day Dams.

4

1/ Yearling Chinook
2/ Sub-Yearling Chinook

be a suitable depth for sampling spring migrants and was later confirmed as suitable for summer migrants as well. With the late April STS installation date and the airlift operational testing, a consistent sampling mode was not possible until the spring migration was nearly at mid-point.

and the second states

Sampling at Lower Monumental Dam commenced about three weeks later than the anticipated fist of May. Preparatory effort in fabrication of the gatewell dipnet, refurbishing the portable fish handling buildings and construction of the safety handrails around the open gatewells, was more time-consuming than expected. Concurrent sampling with the Bio-Sonics hydroacoustics unit was consequently reduced to about one week. Their diel passage profile indicated major passage during the night hours - primarily before 020C hours ¹⁷. We therefore adjusted our dipnet schedule to conform to this, working 1800-0230 hours. Except for unexpected turbine shutdowns, once operational our sampling activities proceeded exceptionally well the remainder of the season.

Supplemental sampling results at Lower Granite and McNary Dams during the month of October are found in Appendix A. These data were collected by the U.S. Army Corps of Engineers dipnetting selected turbine gatewells at these two sites with support provided by various fishery agencies, including NMFS.

SUMMARY

The smolt monitoring project of the National Marine Fishery Service provided data on the seaward migration of juvenile salmon and steelhead at Lower Granite, McNary, John Day, and Lower Monumental Dams during 1985. The numbers of fish sampled by species and brand recaptures were provided to the Water Budget Center for the purpose of evaluating smolt survival, travel time and migrational timing.

RECOMMENDATIONS

- Coordination of all activities affecting sampling/monitoring with those individuals or groups directly involved in the sampling programs is of continuing importance.
- Timely distribution of mark release information to each sampling site is vital.
- 3. Good quality brands on the fish at release will improve potential recognition at recapture sites. This cannot be over-emphasized.
- 1/ Personal communication with Bio-Sonics operators at Lower Monumental Dam.



ACKNOWLEDGEMENTS

Support for this smolt monitoring project came from the region's electrical ratepayers through the Bonneville Power Administration.

We appreciate the assistance of the Northwest and Alaska Fisheries Center, Coastal Zone and Estuarine Studies Division. In particular, the use of the shop facilities and equipment at the Pasco and Rufus Field Stations were especially helpful.

We also wish to thank the U.S. Army Corps of Engineers and especially their on-site biologists and assistants for their cooperation and assistance at each sampling site: Lower Granite, Lower Monumental, McNary and John Day dams.



6

LIBRARY Non-Met Fisherin Soomer Soomer Street 27 Million Balle Fisher Street Mark 98117

LITERATURE CITED

Anonymous, 1985. The Fish Transportation Oversight Team's Annual Work Plan For Transport Operations at Lower Granite, Little Goose, and McNary Dams for Field Year (FY) 1985. Unpublished document.

Johnsen, R.C., C.W. Sims, D.A. Brege, and A.E. Giorgi. 1984. Monitoring 1984. Monitoring of Downstream Salmon and Steelhead at Federal Hydroelectric Facilities. Natl. Mar. Fish. Serv., Seattle, WA. Annual Report to Bonneville Power Administration, November 1984

(Agreement DE-a179-84BP17265). 6p.




Appendix A. 1985 post-season gatewell dipping results at Lower Granite and McNary Dams.

Juvenile salmon

Steelhead

Sockeye

Dam



1/ Obtained from U.S. Army Corps of Engineers.

Chinook

