

NOAA Technical Memorandum NWS WR-119



RELATIVE FREQUENCY OF OCCURRENCE OF WARM SEASON ECHO ACTIVITY AS A
FUNCTION OF STABILITY INDICES COMPUTED FROM THE YUCCA FLAT, NEVADA,
RAWINSONDE

Darryl Randerson
National Weather Service Western Region
Salt Lake City, Utah
June 1977

noaa

NATIONAL OCEANIC AND
ATMOSPHERIC ADMINISTRATION

National Weather
Service



NOAA TECHNICAL MEMORANDA
National Weather Service, Western Region Subseries

The National Weather Service (NWS) Western Region (WR) Subseries provides an informal medium for the documentation and quick dissemination of results not appropriate, or not yet ready, for formal publication. The series is used to report on work in progress, to describe technical procedures and practices, or to relate progress to a limited audience. These Technical Memoranda will report on investigations devoted primarily to regional and local problems of interest mainly to personnel, and hence will not be widely distributed.

Papers 1 to 25 are in the former series, ESSA Technical Memoranda, Western Region Technical Memoranda (WRTM); papers 24 to 59 are in the former series, ESSA Technical Memoranda, Weather Bureau Technical Memoranda (WBTM). Beginning with 60, the papers are part of the series, NOAA Technical Memoranda NWS. Out-of-print memoranda are not listed (inclusive, 1-115).

Papers 2 to 22, except for 5 (revised edition), are available from the National Weather Service Western Region, Scientific Services Division, P. O. Box 11188, Federal Building, 125 South State Street, Salt Lake City, Utah 84147. Paper 5 (revised edition), and all others beginning with 25 are available from the National Technical Information Service, U. S. Department of Commerce, Sills Building, 5285 Port Royal Road, Springfield, Virginia 22151. Prices vary for all paper copy; \$2.25 microfiche. Order by accession number shown in parentheses at end of each entry.

ESSA Technical Memoranda (WRTM)

2. Climatological Precipitation Probabilities. Compiled by Ludianna Miller, December 1965.
3. Western Region Pre- and Post-PP-3 Program, December 1, 1965, to February 20, 1966. Edward D. Diemer, March 1966.
5. Station Descriptions of Local Effects on Synoptic Weather Patterns. Philip Williams, Jr., April 1966 (revised November 1967, October 1969). (PB-17800)
7. Final Report on Precipitation Probability Test Programs. Edward D. Diemer, May 1966.
8. Interpreting the RAREP. Herbert P. Benner, May 1966 (revised January 1967).
11. Some Electrical Processes in the Atmosphere. J. Latham, June 1966.
17. A Digitalized Summary of Radar Echoes within 100 Miles of Sacramento, California. J. A. Youngberg and L. B. Overaas, December 1966.
18. Limitations of Selected Meteorological Data. December 1966.
21. An Objective Aid for Forecasting the End of East Winds in the Columbia Gorge, July through October. D. John Coparanis, April 1967.
22. Derivation of Radar Horizons in Mountainous Terrain. Roger C. Pappas, April 1967.

ESSA Technical Memoranda, Weather Bureau Technical Memoranda (WBTM)

25. Verification of Operational Probability of Precipitation Forecasts, April 1966-March 1967. W. W. Dickey, October 1967. (PB-176240)
26. A Study of Winds in the Lake Mead Recreation Area. R. P. Augulis, January 1968. (PB-177830)
28. Weather Extremes. R. J. Schmidt, April 1968 (revised July 1968). (PB-178928)
29. Small-Scale Analysis and Prediction. Philip Williams, Jr., May 1968. (PB-178425)
30. Numerical Weather Prediction and Synoptic Meteorology. Capt. Thomas D. Murphy, U.S.A.F., May 1968. (AD-673365)
31. Precipitation Detection Probabilities by Salt Lake ARTC Radars. Robert K. Belesky, July 1968. (PB-179084)
35. Probability Forecasting--A Problem Analysis with Reference to the Portland Fire Weather District. Harold S. Ayer, July 1968. (PB-179289)
35. Joint ESSA/FAR ARTC Radar Weather Surveillance Program. Herbert P. Benner and DeVon B. Smith, December 1968 (rev. June 1970). (AD-681857)
36. Temperature Trends in Sacramento--Another Heat Island. Anthony D. Lentini, February 1969. (PB-183055)
37. Disposal of Logging Residues without Damage to Air Quality. Owen P. Cramer, March 1969. (PB-183057)
38. Climate of Phoenix, Arizona. R. J. Schmidt, P. C. Kangleser, and R. S. Ingram, April 1969. (Rev. July 1971; May 1976.) (PB-184295)
39. Upper-Air Lows over Northwestern United States. A. L. Jacobson, April 1969. (PB-184296)
40. The Man-Machine Mix in Applied Weather Forecasting in the 1970s. L. W. Snellman, August 1969. (PB-185068)
42. Analysis of the Southern California Santa Ana of January 15-17, 1966. Barry B. Aronovitch, August 1969. (PB-185670)
43. Forecasting Maximum Temperatures at Helena, Montana. David E. Olsen, October 1969. (PB-185762)
44. Estimated Return Periods for Short-Duration Precipitation in Arizona. Paul C. Kangleser, October 1969. (PB-187763)
46. Applications of the Net Radiometer to Short-Range Fog and Stratus Forecasting at Eugene, Oregon. L. Yee and E. Bates, December 1969. (PB-190476)
47. Statistical Analysis as a Flood Routing Tool. Robert J. C. Burnash, December 1969. (PB-188744)
48. Tsunami. Richard P. Augulis, February 1970. (PB-190157)
49. Predicting Precipitation Type. Robert J. C. Burnash and Floyd E. Hug, March 1970. (PB-190962)
50. Statistical Report on Aeroallergens (Pollens and Molds) Fort Huachuca, Arizona, 1969. Wayne S. Jonsson, April 1970. (PB-191743)
51. Western Region Sea State and Surf Forecaster's Manual. Gordon C. Shields and Gerald B. Burdwell, July 1970. (PB-193102)
52. Sacramento Weather Radar Climatology. R. G. Pappas and G. M. Veliquette, July 1970. (PB-193347)
54. A Refinement of the Vorticity Field to Delineate Areas of Significant Precipitation. Barry B. Aronovitch, August 1970.
55. Application of the SSARR Model to a Basin without Discharge Record. Vail Schermerhorn and Donald W. Kuehl, August 1970. (PB-194394)
56. Areal Coverage of Precipitation in Northwestern Utah. Philip Williams, Jr., and Werner J. Heck, Sept. 1970. (PB-194389)
57. Preliminary Report on Agricultural Field Burning vs. Atmospheric Visibility in the Willamette Valley of Oregon. Earl M. Bates and David O. Chicote, September 1970. (PB-194710)
58. Air Pollution by Jet Aircraft at Seattle-Tacoma Airport. Wallace R. Donaldson, October 1970. (COM-71-00017)
59. Application of PE Model Forecast Parameters to Local-Area Forecasting. Leonard W. Snellman, Oct. 1970. (COM-71-00016)

NOAA Technical Memoranda (NWS WR)

60. An Aid for Forecasting the Minimum Temperature at Medford, Oregon. Arthur W. Fritz, October 1970. (COM-71-00120)
62. Forecasting the Catalina Eddy. Arthur L. Eichelberger, February 1971. (COM-71-00223)
63. 700-mb Warm Air Advection as a Forecasting Tool for Montana and Northern Idaho. Norris E. Woerner, February 1971. (COM-71-00349)
64. Wind and Weather Regimes at Great Falls, Montana. Warren B. Price, March 1971.
66. A Preliminary Report on Correlation of ARTCC Radar Echoes and Precipitation. Wilbur K. Hall, June 1971. (COM-71-00829)
69. National Weather Service Support to Soaring Activities. Ellis Burton, August 1971. (COM-71-00956)
71. Western Region Synoptic Analysis-Problems and Methods. Philip Williams, Jr., February 1972. (COM-72-10433)
74. Thunderstorms and Hot Days Probabilities in Nevada. Clarence M. Sakamoto, April 1972. (COM-72-10554)
75. A Study of the Low Level Jet Stream of the San Joaquin Valley. Ronald A. Willis and Philip Williams, Jr., May 1972. (COM-72-10707)
76. Monthly Climatological Charts of the Behavior of Fog and Low Stratus at Los Angeles International Airport. Donald M. Gales, July 1972. (COM-72-11140)
77. A Study of Radar Echo Distribution in Arizona During July and August. John E. Hales, Jr., July 1972. (COM-72-11136)
78. Forecasting Precipitation at Bakersfield, California, Using Pressure Gradient Vectors. Earl T. Riddough, July 1972. (COM-72-11146)
79. Climate of Stockton, California. Robert C. Nelson, July 1972. (COM-72-10920)
80. Estimation of Number of Days Above or Below Selected Temperatures. Clarence M. Sakamoto, October 1972. (COM-72-10021)
81. An Aid for Forecasting Summer Maximum Temperatures at Seattle, Washington. Edgar G. Johnson, Nov. 1972. (COM-73-10150)
83. A Comparison of Manual and Semiautomatic Methods of Digitizing Analog Wind Records. Glenn E. Rasch, March 1973. (COM-73-10669)
84. Southwestern United States Summer Monsoon Source--Gulf of Mexico or Pacific Ocean? John E. Hales, Jr., March 1973. (COM-73-10769)
86. Conditional Probabilities for Sequences of Wet Days at Phoenix, Arizona. Paul C. Kangleser, June 1973. (COM-73-11264)
87. A Refinement of the Use of K-Values in Forecasting Thunderstorms in Washington and Oregon. Robert V. G. Lee, June 1973. (COM-73-11276)
89. Objective Forecast of Precipitation over the Western Region of the United States. Julia N. Paegle and Larry P. Kjarulff, September 1973. (COM-73-11946/3AS)
90. A Thunderstorm "Warm Wake" at Midland, Texas. Richard A. Wood, September 1973. (COM-73-11845/AS)
91. Arizona "Eddy" Tornadoes. Robert S. Ingram, October 1973. (COM-73-10465)

NOAA Technical Memorandum NWS WR-119

RELATIVE FREQUENCY OF OCCURRENCE OF WARM SEASON ECHO
ACTIVITY AS A FUNCTION OF STABILITY INDICES COMPUTED
FROM THE YUCCA FLAT, NEVADA, RAWINSONDE


Darryl Randerson
Nuclear Support Office
National Weather Service
Las Vegas, Nevada

June 1977

UNITED STATES
DEPARTMENT OF COMMERCE
Juanita M. Kreps, Secretary

NATIONAL OCEANIC AND
ATMOSPHERIC ADMINISTRATION
Robert M. White, Administrator

NATIONAL WEATHER
SERVICE
George P. Cressman, Director



CONTENTS

	<u>Page</u>
Figures	iii
Abstract	1
I. Introduction	1
II. Procedure	2
III. Results	4
IV. Summary	7
V. Appendix A	7
VI. Acknowledgments	10
VII. References	10

FIGURES

Page

Figure 1. Area considered in the echo survey for southern Nevada and adjacent regions. The shaded boxes represent the specific areas for which the relative frequency of the occurrence of an echo was calculated as a function of both the K and Z indices. Each grid point represents the center of a 28 by 28 km box. 3

Figure 2. Percentage probability of radar detection of surface precipitation during summertime (from Western Region Technical Attachment 73-11, dated 3-20-73), 4

Figure 3. Relative frequency of occurrence of an echo-day for specified areas between local midnight and local midnight as a function of K and Z index values calculated from the Yucca Flat 1200Z sounding. The K curve is represented by the solid line, the Z curve by the dotted line. Values plotted next to the x's are the number of days in each K category and the numbers next to the o's are the number of days in each Z category. 5

Figure 4. Z index versus the percentage frequency of occurrence of a cumulonimbus cloud being observed in the vicinity of the NTS. Each + point represents the median Z value contained within groups of 100 ranked Z values. The range of the 100 Z values in each group is represented by lines paralleling the abscissa. 10

RELATIVE FREQUENCY OF OCCURRENCE OF WARM SEASON ECHO ACTIVITY
AS A FUNCTION OF STABILITY INDICES COMPUTED FROM
THE YUCCA FLAT, NEVADA, RAWINSONDE

Darryl Randerson
Nuclear Support Office
National Weather Service

ABSTRACT. A radar echo survey for two warm seasons is used to determine the relative frequency of occurrence of an echo in six selected areas. These areas include the Las Vegas Valley, Lake Mead, and the Spring Mountains, all located in extreme southern Nevada. Also included are the Tonopah and Nevada Test Site areas as well as the Cedar City, Utah, area. The occurrence of an echo in these areas is related to both the K and Z indices, calculated from the Yucca Flat, Nevada, 1200Z sounding. The relative frequency of occurrence of an echo was determined for various categories of K and Z. The resulting charts should have practical value for estimating the probability of the occurrence of moist convection in the specified areas.

I. INTRODUCTION

In a previous study (Randerson, 1976), documentation was provided of the spatial variation of moist convection as detected by Air Route Traffic Control (ARTC) radars in the vicinity of southern Nevada and adjacent areas. The study showed that in some areas of high detectability, approximately twice as much echo activity occurs over high terrain as over the valleys.

In a separate study (Randerson, 1977), both regression analysis and discriminant analysis were used to develop a single-station cumulonimbus (Cb) prediction equation (Z index) for the Nevada Test Site (NTS).[†] Using 10 years of rawinsonde data collected at Yucca Flat, Nevada, regression analysis was used to select the most important predictors to be input to a discriminant analysis program which generated the coefficients for the Z-index equation. The regression equation which selected the predictors accounts for 43% of the variance in the predictand. Based on the same data sample, the K index (George, 1960) explains only

[†]See Appendix A.

33% of the variance of the predictand. Verification of the performance of the Z index on independent data demonstrates it provides a meaningful first approximation to the probable development of local *Cb activity* during the period June through September. In this report, no attempt is made to demonstrate the superiority of one index over the other. The K index is included only because of its popularity and availability.

In this study, both the Z and K values of Yucca Flat are related to the occurrence of *echo activity* as detected by the ARTC radars. Consequently, the spatial variability in the relative frequency of occurrence of moist convection can be determined as a function of an index derived from a single upper-air sounding.

II. PROCEDURE

Hourly radar-echo data were extracted from microfilm records of the Western Region RAFAX transmissions. Only the 1971 and 1972 warm season (June through September) hourly RAFAX charts were surveyed (Randerson, 1976). A total of 238 days were included in the survey. Of these days, 68 were echoless and 10 had missing rawinsonde data.

The grid defined in Figure 1 was used as an overlay to extract the echo data from the microfilm record. Each grid point represents the center of a 28- by 28-km box. The overlay was superimposed on the projected image of each hourly RAFAX chart as it appeared on the screen of a microfilm reader. If *any portion* of an echo appeared within a grid square, an echo was counted as occurring within that square during the specified hour. No effort was made to classify the echo according to intensity or to specify what percentage of each grid box was filled by an echo at a given time. Thereby, the echo inventory only consisted of determining if any portion of an echo occurred or did not occur in a grid square.

Since the objective of the study was to determine if an echo occurred within a specified area during the 24-hour period from local midnight to local midnight, the hourly echo data were summarized for each individual 28- by 28-km box for the 24-hour period. The summarized echo data were printed out in a gridded format to simplify the survey for the daily occurrence of an echo-day.

Warm season echo activity, within the area of Figure 1, goes through a typical diurnal oscillation (Randerson, 1976). Most of the echo activity occurs in midafternoon with minimum activity between local midnight and 0800 LST. Consequently, the echo-day data set does contain some days for which the echo activity occurred before the local 1200Z (0500 LST) sounding was taken; however, the number of these events is small compared with the large number of occurrences between 0500 LST and local midnight. For example, in the Yucca Flat area, only 6 to 7% of the echoes occur between local midnight and the time the 1200Z sounding is taken.




Figure 1. Area considered in the echo survey for southern Nevada and adjacent regions. The shaded boxes represent the specific areas for which the relative frequency of the occurrence of an echo was calculated as a function of both the K and Z indices. Each grid point represents the center of a 28 by 28 km box.

The specific areas surveyed are identified in Figure 1 by shading. These areas were selected primarily for their proximity to regions of high detectability (Figure 2) as well as for population density and recreational use. The Nevada Test Site (NTS) was included because the National Weather Service--Nuclear Support Office (NWS-NSO) is responsible for predicting the weather for this facility.

In Figure 1 notice that the NTS, the Spring Mountains (SPM), Lake Mead (LMD), and the Cedar City, Utah (CDC), areas are all equal in size--3136 km². However, the Las Vegas Valley (LAS) covers an area of 4704 km² while the Tonopah, Nevada (TPH), area covers 7056 km².




Figure 2. Percentage probability of radar detection of surface precipitation during summertime (from Western Region Technical Attachment 73-11, 3-20-73).

III. RESULTS

Both K and Z indices were calculated from the 1200Z soundings for Yucca Flat. These values were then tabulated along with the echo-day information for each of the six selected areas. Thereby, the relative frequency of occurrence of an echo-day within a given area could be easily computed after summarizing the number of occurrences (and non-occurrences) for each of the six areas shown in Figure 1.

The range of the K values was from 40 to -11 while the Z index values ranged from 17 to -5. However, due to the limited number of days with $K > 35$ and $K < -3$, occurrences in these ranges were not used to draw the free-hand curves in Figure 3. These values included four days for $K > 35$ and six days for $K < -3$. Only two days of Z were not used and these were for $Z > 15$.




Figure 3. Relative frequency of occurrence of an echo-day for specified areas between local midnight and local midnight as a function of K and Z index values calculated from the Yucca Flat 1200Z sounding. The K curve is represented by the solid line, the Z curve by the dotted line. Values plotted next to the x's are the number of days in each K category and the numbers next to the o's are the number of days in each Z category.

Due to the limited size of the sample, both index values were categorized into groups of three values each. For example, the K index values ranged from K = 34 (includes K's of 35, 34, and 33) to K = -2 (includes K's of -1, -2, and -3). The Z categories ranged from Z = -4 (includes Z's of -5, -4, and -3) to Z = 14 (includes Z's of 15, 14, and 13). Consequently the K values consisted of 13 categories while the Z values contained only 7 categories.

Results of the survey are shown in Figure 3 which represents the relative frequency of occurrence of echo-days as a function of both the K and Z index as calculated from the 1200Z Yucca Flat sounding. The curve of the K index appears on the left-hand side of each chart while the Z curve is on the right-hand side. Both S-shaped curves are free-hand renditions. The values plotted near each data point represent the total number of days in each category. Charts of both indices are presented for the Las Vegas Valley (LAS), the Lake Mead area (LMD), the Spring Mountains (SPM), the Nevada Test Site (NTS), Tonopah (TPH), and Cedar City (CDC).

Caution should be used in interpreting the charts in Figure 3. First, notice the opposing orientation of the indices--negative values of Z correspond with large relative frequencies while large positive values of K correspond with large relative frequencies. Second, the indices are on different scales so that one should not use the slopes of the curves to conclude that one index is superior to the other. The diagrams are presented only to portray the relative frequency of occurrence of an echo-day versus the two different stability indices.

The charts in Figure 3 show that for a Yucca Flat K value of 30, the relative frequency of occurrence for an echo ranges from near 65% for the LMD area to near 95% for the CDC area. For a Z value of 0, the charts show the frequency of occurrence ranges from near 40% for TPH to near 80% for the CDC area.

The relative frequency of occurrence of echo-days as a function of K and Z was also determined for the four grid points in the 90% detectability area in the southwest corner of the grid (Figure 2). This hilly area is in the Mojave Desert. Results indicate that the Yucca Flat, 1200Z, sounding is also representative for this area; however, the frequencies of occurrence are much lower. For example, for a K of 30, the frequency is 40% and for a Z of 0 it is 30%. Comparing these frequencies with those corresponding with the same K and Z values for the other areas helps emphasize the east-west gradient of the frequency of occurrence of moist convection across the area (Figure 1).

Two seasons of echo data is a small sample, especially in a desert area where the yearly variation in moist convection can be large. To add credibility to the small sample, the Z index curve for the NTS was compared with a similar curve developed from a larger data base, but for the relative frequency of occurrence of *Cb days* (Randerson, 1977). The developmental data base used to relate the Z index to Cb days was

compiled from the 1200 GMT, Yucca Flat, rawinsonde observations and hourly surface observations taken during 10 consecutive warm seasons (June-September) 1962-1971. The resulting curve for Cb days is not included in the NTS figure because there is little difference between the two curves--both curves would lie approximately on top of each other.

IV. SUMMARY

A description is given of a simple climatological method of determining the relative frequency of occurrence of echo-days for five different areas in southern Nevada and for Cedar City, Utah. The relative frequency of occurrence comes from a radar echo survey of moist convection in the selected areas. The occurrence of echo-days in the selected areas is related to the 1200Z, Yucca Flat, K and Z indices, thereby permitting the frequency of occurrence of echo-days to be computed for various categories of K and Z. The resulting charts should have practical value for estimating the probability of the occurrence of moist convection in the specified areas.

The results confirm that moist convection is observed more frequently over high terrain than over valleys and that in the desert area studied, the frequency with which echoes are observed increases from west to east. Furthermore, the study indicates that upper-air data from a single station are representative of a rather large area, suggesting the grid of rawinsonde stations is adequate.

V. APPENDIX A

The Z-index developmental data set was compiled from hourly surface observations and from the 1200 GMT, Yucca Flat, Nevada (UCC), rawinsonde observations taken in the 10 consecutive warm seasons (June through September) 1962-1971. Out of a possible total of 1220 observational days, 1079 were available for use in developing the Z index. Of these 1079 days, 309 were Cb days and 770 were non-Cb days. For the UCC weather station, this 10-yr sample shows that approximately 70% of all the Cb days (includes thunderstorm days) occur during the period June through September.

The dependent variable, Cb days, was catalogued from the hourly surface observations for UCC. Corresponding independent variables (predictors) were selected from only the 1200 GMT rawinsonde data. Consequently, an implicit assumption in the Z index is that the basic vertical structure of the atmosphere remains unchanged throughout the corresponding day. The potential predictors were temperature, dew-point depression, dew-point temperature, u and v components of the wind, height (station pressure for the surface), the K index, the Total Totals index (Miller, 1967), and the SWEAT index (Bidner, 1971). The variables were specified for the surface (near 880-mb level) and for 50-mb intervals from the 850-mb level through the 500-mb level.

To select the set of predictors for input to the discriminant analysis program, all the data were input to a regression analysis routine (WRAP) so that the variables would be selected objectively. Using the number of hours of Cb activity as the dependent variable, the

WRAP program scanned the independent data and calculated the reduction in the regression sum of the squares that would occur as each independent variable was deleted from the analysis. The minimum reduction in the regression sum of the squares was then determined and divided by the error sum of the squares--a ratio that has an f distribution. This value of f was tested against the 95% probability level. This probability level was used in deleting variables from the regression and it can be expressed as the area under the f curve from zero to f_0 , where f_0 is the significant value of f . If the value was not significant, that independent variable was deleted from the analysis and the process repeated until the deletion of an independent variable would have resulted in a significant reduction of the variance explained. This selection process ended with nine predictors remaining. The resulting regression equation accounts for approximately 43% of the variance of the predictand. Based on the same data sample, the K index explains only 33% of the variance of the predictand. The nine predictors selected from the rawinsonde data were the surface pressure, surface temperature, surface dewpoint depression, 850-mb temperature, 800-mb dew-point depression, 700-mb height, 500-mb temperature, 500-mb dew-point temperature, and the u component of the 500-mb wind. Notice that the K, Total Totals, and SWEAT indices were all rejected by WRAP.

After objectively selecting the predictors, one is tempted to attribute some physical significance to the selected parameters and to offer physical reasons why other variables remain unselected. However, such an analysis is difficult to make and any conclusions reached are subject to question because of the inherent redundancy in the informational content of meteorological data.

The data for the nine predictors (v_i) were input to a discriminant analysis program which computes coefficients (a_i) of the linear function,

$$Z^* = a_1 v_1 + a_2 v_2 + \dots + a_n v_r$$

such that the difference between an average Z^* for non-occurrences and an average Z^* for occurrences is a maximum. Unfortunately, the discriminant analysis program was limited to a sample size of not more than 300 cases in each of the two groups (occurrence and non-occurrences). The first 300 cases in each group were selected from the data base and run with the nine predictors selected by WRAP to produce the coefficients for the linear discriminant function, Z^* . The resulting regression equation for Z^* , is

$$\begin{aligned} Z^* = & 165.19V_1 - 14.63V_2 + 11.73V_3 + 31.52V_4 + 38.22V_5 - 17.30V_6 \\ & + 85.89V_7 + 12.69V_8 - 12.85V_9 \end{aligned} \quad (1)$$

where,

- V_1 = surface pressure (mb)
- V_2 = surface temperature ($^{\circ}$ C)
- V_3 = surface dew-point depression ($^{\circ}$ C)
- V_4 = 850-mb temperature ($^{\circ}$ C)
- V_5 = 800-mb dew-point depression ($^{\circ}$ C)
- V_6 = 700-mb height (m)
- V_7 = 500-mb temperature ($^{\circ}$ C)
- V_8 = u component of the 500-mb wind (kts)
- V_9 = 500-mb dew-point temperature ($^{\circ}$ C)

The data base used to derive Eq. 1 consisted of 309 occurrences (Cb days) and 770 non-occurrences so that the 300 occurrences came from essentially the entire data base. However, the first 300 non-occurrences included that portion of the data base from 1 June 1962 through 24 June 1966. The discriminant analysis program ranked these 600 cases in descending order and each case was identified as corresponding to an occurrence (YES) or non-occurrence (NO) of a Cb day. Using the ranked index values and collecting these values into groups of 100 cases each, the relative frequency of occurrence of a Cb day was computed for each group. One overlapping group of 100 cases was added near the 57% level to provide a data point near the inflection point of the curve in Figure 4. The percentage of the YES cases was plotted at the median value of the Z index for each group of 100 cases. Plotted values yield an S-shaped curve which was drawn freehand to produce the subjective curve in Figure 4. This curve allows you to determine the relative frequency of Cb activity being observed at some time during the day based on information available in the 1200 GMT UCC sounding on that day. When applied to a forecasting situation, the Z index provides a first approximation to the probability of moist convection occurring on the given day.

In Figure 4, the values of Z^* have been modified by use of the expression

$$Z = 0.01 (Z^* - 93200) \quad (2)$$

so that for a relative frequency (probability, P) of 50%, $Z = 0$. In addition, for probability levels greater than 50%, Z will be negative. In general, for $Z < -4.0$, $P > 90\%$ and for $Z > 5.0$, $P < 10\%$.




Figure 4. Z index versus the percentage frequency of occurrence of a cumulonimbus cloud being observed in the vicinity of the NTS. Each + point represents the median Z value contained within groups of 100 ranked Z values. The range of the 100 Z values in each group is represented by lines paralleling the abscissa.

VI. ACKNOWLEDGMENTS

My sincere thanks to the meteorologists at the Nuclear Support Office for their many helpful comments. A special thanks to the meteorological technicians who conscientiously tabulated the echo data. Also, the drafting services of Mr. Jack L. Diekey are appreciated.

VII. REFERENCES

- Bidner, A., 1971: The AFGWC Severe-Weather-Threat (SWEAT) index; (a preliminary report). U.S. Air Weather Service, *Tech. Report 242*, U.S. Air Force Global Weather Central, Offutt, AFB, Nebraska, pp. 229-231.
- George, J. J., 1960: *Weather Forecasting for Aeronautics*, New York, Academic Press, 673 pp. (see pp. 411).

Miller, R. C., 1967: Notes on analysis and severe storm forecasting procedures of the Military Weather Warning Center. *Tech. Report 200*, Air Weather Service (MAC), USAF, Scott, AFB, July 1967.

Randerson, D., 1976: Summertime radar echo distribution of moist convection over southern Nevada and adjacent areas for 1971 and 1972. *NOAA Tech. Memo. ERL ARL-58*, 37 pp.

_____, 1977: Determining the relative frequency of occurrence of local cumulonimbus activity through discriminant analysis. *Mon. Wea. Rev.*, 105, (in press).

NOAA Technical Memoranda NWS WR (Continued)

- 92 Smoke Management in the Willamette Valley. Earl M. Bates, May 1974. (COM-74-11277/AS)
- 93 An Operational Evaluation of 500-mb Type Stratified Regression Equations. Alexander E. MacDonald, June 1974. (COM-74-11407/AS)
- 94 Conditional Probability of Visibility Less than One-Half Mile in Radiation Fog at Fresno, California. John D. Thomas, August 1974. (COM-74-11555/AS)
- 95 Climate of Flagstaff, Arizona. Paul W. Sorenson, August 1974. (COM-74-11678/AS)
- 96 Map Type Precipitation Probabilities for the Western Region. Glenn E. Rasch and Alexander E. MacDonald, February 1975. (COM-75-10428/AS)
- 97 Eastern Pacific Cut-Off Low of April 21-28, 1974. William J. Alder and George R. Miller, January 1976. (PB-250711/AS)
- 98 Study on a Significant Precipitation Episode in the Western United States. Ira S. Brenner, April 1975. (COM-75-10719/AS)
- 99 A Study of Flash Flood Susceptibility--A Basin in Southern Arizona. Gerald Williams, August 1975. (COM-75-11360/AS)
- 100 A Study of Flash-Flood Occurrences at a Site versus Over a Forecast Zone. Gerald Williams, August 1975. (COM-75-11404/AS)
- 102 A Set of Rules for Forecasting Temperatures in Napa and Sonoma Counties. Wesley L. Tuft, October 1975. (PB-246 902/AS)
- 103 Application of the National Weather Service Flash-Flood Program in the Western Region. Gerald Williams, January 1976. (PB 253 053/AS)
- 104 Objective Aids for Forecasting Minimum Temperatures at Reno, Nevada, During the Summer Months. Christopher D. Hill, January 1976. (PB 252 866/AS)
- 105 Forecasting the Mono Wind. Charles P. Ruscha, Jr., February 1976. (PB 254650)
- 106 Use of MOS Forecast Parameters in Temperature Forecasting. John C. Plankinton, Jr., March 1976. (PB 254649)
- 107 Map Types as Aid in Using MOS PoPs in Western United States. Ira S. Brenner, August 1976. (PB 259594)
- 108 Other Kinds of Wind Shear. Christopher D. Hill, August 1976. (PB 260437/AS)
- 109 Forecasting North Winds in the Upper Sacramento Valley and Adjoining Forests. Christopher E. Fontana, September 1976.
- 110 Cool Inflow as a Weakening Influence on Eastern Pacific Tropical Cyclones. William J. Denney, November 1976. (PB 264655/AS)
- 111 Operational Forecasting Using Automated Guidance. Leonard W. Snellman, February 1977.
- 112 The MAN/MOS Program. Alexander E. MacDonald, February 1977. (PB 265941/AS)
- 113 Winter Season Minimum Temperature Formula for Bakersfield, California, Using Multiple Regression. Michael J. Oard, February 1977.
- 114 Tropical Cyclone Kathleen. James R. Fors, February 1977.
- 115 Program to Calculate Winds Aloft Using a Hewlett-Packard 25 Hand Calculator. Brian Finke, February 1977.
- 116 A Study of Wind Gusts on Lake Mead. Bradley Colman, April 1977.
- 117 The Relative Frequency of Cumulonimbus Clouds at the Nevada Test Site as a Function of K-Value. R. F. Quiring.
- 118 Moisture Distribution Modification by Upward Vertical Motion. Ira S. Brenner, April 1977.

NOAA SCIENTIFIC AND TECHNICAL PUBLICATIONS

NOAA, the *National Oceanic and Atmospheric Administration*, was established as part of the Department of Commerce on October 3, 1970. The mission responsibilities of NOAA are to monitor and predict the state of the solid Earth, the oceans and their living resources, the atmosphere, and the space environment of the Earth, and to assess the socioeconomic impact of natural and technological changes in the environment.

The six Major Line Components of NOAA regularly produce various types of scientific and technical information in the following kinds of publications:

PROFESSIONAL PAPERS — Important definitive research results, major techniques, and special investigations.

TECHNICAL REPORTS—Journal quality with extensive details, mathematical developments, or data listings.

TECHNICAL MEMORANDUMS — Reports of preliminary, partial, or negative research or technology results, interim instructions, and the like.

CONTRACT AND GRANT REPORTS—Reports prepared by contractors or grantees under NOAA sponsorship.

TECHNICAL SERVICE PUBLICATIONS—These are publications containing data, observations, instructions, etc. A partial listing: Data serials; Prediction and outlook periodicals; Technical manuals, training papers, planning reports, and information serials; and Miscellaneous technical publications.

ATLAS—Analysed data generally presented in the form of maps showing distribution of rainfall, chemical and physical conditions of oceans and atmosphere, distribution of fishes and marine mammals, ionospheric conditions, etc.



Information on availability of NOAA publications can be obtained from:

**ENVIRONMENTAL SCIENCE INFORMATION CENTER
ENVIRONMENTAL DATA SERVICE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
U.S. DEPARTMENT OF COMMERCE**

**3300 Whitehaven Street, N.W.
Washington, D.C. 20235**