NOAA

UNITED STATES - GULF COAST

FLORIDA

SAND KEY TO REBECCA SHOAL

Formerly C&GS 1252, 1st Ed., July 1912 C-1961-777 KAPP 356

SOUNDINGS IN FEET

11439

LORAN-C OVERPRINTED

NOTE X

The 12 nautical mile territorial sea was established by Presidential Proclamation 5928, December 27, 1988, and is also the outer limit of the U.S. contiguous zone for the application of domestic law. The 3 nautical mile line previously identified as the outer limit of the territorial sea, is retained because the proclamation states that it does not alter existing State or Federal law. The 9 nautical mile natural resources boundary off Texas, the Gulf coast of Florida, and Puerto Rico, and the 3 nautical mile line elsewhere remain the inner boundary of the Federal fisheries jurisdiction and the limit of states' jurisdiction under the Submerged Lands Act (P.L. 83-31, 67 Stat. 29, March 22, 1953). These maritime limits are subject to modification, as represented on future charts. The lines shown on the most recent chart edition take precedence.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation

Mercator Projection
Scale 1:80,000 at Lat. 24°35′
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83) which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84) Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.533" northward and 0.641" eastward to agree with this chart.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 5. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 7th Coast Guard District in Miami, Fla., or at the Office of the District Engineer, Corps of Engineers in Jacksonville, Fla.
Refer to charted regulation section numbers

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

TIDAL INFORMATION

Place	Height referred to datum of soundings (MLLW)			
	Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
Sand Key Light	feet 1.7	feet 1.4	feet 0.2	feet -1.5

(585) (Latest information available)

COLREGS: 80,740 (see note A)

International Regulations for Preventing Collisions at Sea, 1972. The entire area of this chart falls seaward of the COLREGS Demarcation line.

For Symbols and Abbreviations see Chart No. 1

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Key West, Fla. WXJ-95 162.40 MHz

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (NCS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910 - 3282.

HEIGHTS

Heights in feet above Mean High Water.

NOTE C

PROHIBITED AREAS
(Areas to be avoided)

Under the Florida Keys National Marine Sanctuary and Protection Act, Pub. L. 101-605 and IMO advisory SN/Circ 145, these areas are to be avoided by tank vessels and vessels greater than 50 meters in length

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey with additional data from the U.S. Coast Guard.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 5 for important supplemental information.

Nautical Miles 0 1 2 3 4 5 6
Yards 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000
Meters 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables are charted, and when anchoring, dragging or trawling.

Covered wells may be marked by lighted or unlighted buoys.

NOTE B

Area is open to unrestricted surface navigation but all vessels are cautioned neither to anchor, dredge, trawl, dry scallop, Bottom nor conduct any other similar type of operation because of residual danger from mines on the bottom.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS

Report all sightings of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

Nautical Chart Catalog No.: 1- Panel O

CONTINUED ON CHART 11434

JOINS CHART 11442

LORAN LINEAR INTERPOLATOR

MICROSECONDS 100 80 60 40 20 0

LORAN-C GENERAL EXPLANATION

LORAN-C FREQUENCY 100kHz
PULSE REPETITION INTERVAL ..... 79,800 Microseconds
7980

STATION TYPE DESIGNATORS: (Not individual station letter designators)
M ..... Master
W ..... Secondary
X ..... Secondary
Y ..... Secondary
Z ..... Secondary

EXAMPLE: 7980-X

RATES ON THIS CHART

7980-W 7980-X 7980-Y 7980-Z

Loran-C correction tables published by the National Imagery and Mapping Agency or others should not be used with this chart. The lines of position shown have been adjusted to conform to charted data. Every effort has been made to meet the 1/4 nautical mile accuracy criteria established by the U.S. Coast Guard. Mariners are cautioned not to rely solely on the lattices in inshore waters.

24th Ed., Dec 13/97

11439
LORAN-C OVERPRINTED

CAUTION
This chart has been corrected from the Notice to Mariners published weekly by the National Imagery and Mapping Agency and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner

Published at Washington, D. C.
U. S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FEET

FATHOMS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
FEET 6 12 18 24 30 36 42 48 54 60 66 72 78 84 90 96 102
METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Sand Key to Rebecca Shoal
SOUNDINGS IN FEET - SCALE: 1:80,000

11439
LORAN-C OVERPRINTED

NSN 7642014010141
NOAA STOCK NO. 11HAA11439

ED NO. 24