NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service stations listed below provide continuous marine weather broadcasts. The range of reception is variable, but for planning purposes is usually 20 to 40 miles from the antenna site.

East Point, Fla	WWF-66	162.55 MHz
Panama City, Fla	KSG-97	162.55 MHz
Tallahassee,Fla	KHA-21	162.40 MHz

BROADCASTS OF MARINE WEATHER FORECASTS AND WARNINGS BY MARINE RADIOTELEPHONE STATIONS

CITY	STATION	FREQ.	BROADCAST TIMES	SPECIAL WARNING
Mobile, Ala.	WLO	2512 kHz 6501.5 kHz 4357.5 kHz 13119.6 kHz 22757.6 kHz	6:00 AM, 7:00 PM & Midnight	On receipt
		(Ch 29) 161.85 MHz (Ch 09) 161.50 MHz (Ch 77) 161.93 MHz (Ch 09) 161.5 MHz	6:00 & 11:00 AM 5:00 & 11:00 PM	
St. Petersburg, Fla.	NMA-21	2670 kHz 4426 kHz	8:20 AM & 7:20 PM	*On receipt
Panama City, Fla.	NOO-7	2670 kHz 4426 kHz	3:00 AM 3:05, 5:05 & 9:03 PM 4:35 & 10:35 AM 4:35 PM	On receipt On receipt

* Preceded by announcement on 2182 kHz and 156.8 MHz

Distress calls for small craft are made on 2182 kHz or channel 16 (156.80 MHz) VHF.

NAUTICAL CHART DIAGRAM



NO.	LOCATION	DEPTH	SERVICES	SUPPLIES
1	SAN JOSE LODGE	6	3	3
2	PORT ST JOE MARINA	4½	4	4
3	SHIP OF FOOLS	4½	4	4
10	APALACH BAY R-2-S	6	4	4
11	MILLER MARINE	20	14	3
12	J.J.'S GINGER	16	16	
14	RANSON MN & MAR	18	10	3
15	APALACHICOLA MARINA	18	18	4
16	SEAFOOD DOCK	10	6	3

THE LOCATIONS OF THE ABOVE PUBLIC MARINE FACILITIES ARE SHOWN ON THE CHART BY LARGE MAGENTA NUMBERS. THE TABULATED "APPROACH DEPTHS(DEP)" IS THE DEPTH AVAILABLE TO THE NEAREST NATURAL OR DREDGED CHANNEL TO THE FACILITY. THE TABULATED "PUMPING STATION" IS DEFINED AS FACILITIES AVAILABLE FOR PUMPING OUT BOAT HOLD TANKS.

FACILITIES

Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation.

MARINE WEATHER FORECASTS
NATIONAL WEATHER SERVICE

	TELEPHONE NUMBER	OFFICE HOURS
Tampa Bay, FL	*(813) 645-2506	24 hours daily
Tallahassee, FL	(850) 942-8833	8:00 AM - 5:00 PM (Mon - Fri.)
Mobile, AL	*(334) 633-5466	24 hours daily
	(334) 633-5440	8:00 AM - 2:00 PM (Mon - Fri.)

*Recorded

PRINT-ON-DEMAND CHARTS

NOAA and its private partners, CoastGeoTech, offer this chart updated with the latest Notice to Mariners, USCG notices and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional charts. To order, or for more information, contact charts.orders@NOAA.gov, call 1-800-638-4493, http://NauticalCharts.gov, help@NauticalCharts.gov, or CoastGeo's at 1-877-GEOMART, http://CoastGeoTech.com, or help@CoastGeoTech.com.

INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts, and the exact meaning of an aid to navigation may not be clear unless the appropriate chart is consulted. Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways.

When following the Intracoastal Waterway eastward from Carrabelle, FL to Brownsville, TX, aids with odd numbers should be kept on the starboard side of the vessel and aids with even numbers should be kept on the port side of the vessel.

A horizontal yellow band provides no lateral significance but serves only to identify navigation as marking the Intracoastal Waterway.

HORIZONTAL DATUM

The horizontal datum for this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System of 1984 (WGS 84). Geographic positions referred to North American Datum of 1927 must be corrected for average of 0.1 nautical mile northwest and 0.2NC eastward to agree with this chart.

INTRACOASTAL WATERWAY

Project Depth
12 feet Carrabelle, FL to Brownsville, TX.
The controlling depths are published periodically in the U.S. Coast Guard Local Notice to Mariners.

Distances
The Waterway is indicated by a magenta line. Mileage distances shown along the Waterway are in Statute Miles, based on zero at Harvey Lock, LA, and are indicated thus: 1000.
Distances between navigation aids are in International Nautical Miles and are given in U.S. Coast Pilot 5.
Courses are TRUE and must be CORRECTED for any variation and compass deviation.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

PUBLIC BOATING INSTRUCTION PROGRAMS

The United States Power Squadrons (USPS) and U.S. Coast Guard Auxiliary (USCGAUX), national organizations of boatmen, conduct extensive boating instruction programs, including courses in piloting and seamanship. For information regarding these educational courses, contact the following sources:
USPS - Local Squadron Commander or USPS Headquarters, Post Office Box 30423, Raleigh, NC 27622-0423 (1-888-367-8777).
USCGAUX - Area Commodore, 1 Poydras Street, New Orleans, LA 70130-3396, 504-589-2837 or USCG Headquarters (G-BAUL, Washington, D.C. 20593-0001.

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 5 for important supplemental information.

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner.

ABBREVIATIONS (For complete list of symbols and abbreviations, see Chart No. 1.)

Aids to navigation lights are red or white (reverse indicated)

ABPA automated	R pivot	Mo mono-octe	R 5% adio tower
Al alternating	Q rapid/quick	N red	Hor rotating
Bn beacon	Qk quick	Ob obscured	Ra radiobeacon
Bn beacon	Qk quick	Ob obscured	Ra radiobeacon
C can	M nautical mile	Or orange	SRC sector
Ch daytime	Mo morse code	Pk pink	SI sl. visible
F fixed	MOBC Bn motorboat towel	R red	W white
H flashing	Mkr marker	Re ref radar refractor	WHG whistle
		R Bn radiobeacon	Y yellow

Bottom characteristics

abbreviations are used as follows:	Co coral	gr gray	Oys oysters
ge broken	S gravel	h hard	Rk rock
Cy clay	Gls glass	M mud	S sand

Miscellaneous

ADN authorized	Obstr obstruction	PD position doubtful
Dep depth doubtful	Pos position approximate	Subm submerged
Rock, rock, obstruction, or tree exact clear to the depth indicated.		
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.		
OUTAGE: Intracoastal Waterway Aid Reporting Outages at Sea, 1972.		
Zemanacion lines are shown thus: ~~~~~		


11402
Formerly 888 SC, 1st Ed., 1978; AAPP 140
Nautical Chart Catalog No., 1 Panel F
85° 10'
85° 00'
PORT ST JOE
(see note C)
APALACHICOLA RIVER
The controlling depth from Jackson River to the Chattahoochee River was 7 feet.
May 1988
The channel is marked by daybeacons from Jackson River to the Chattahoochee River.
NOTE
Shoaling exists to various depths in the Apalachicola River between Buoys 13 and Buoy 24.
ST MARKS ISLAND
SCALE 1:40,000
Nautical Miles
Statute Miles
Yards
Meters
LOGARITHMIC SPEED SCALE
To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.6 nautical miles run in 15 minutes, the speed is 18.4 knots
NOTE C
Port St. Joe is in the Eastern Standard Time Zone.
ST JOSEPH BAY
(see chart 11393)
CAPE SAN BLAS
GULF OF MEXICO
ST VINCENT ISLAND
ST VINCENT SOUND
APALACHICOLA BAY
APALACHICOLA
APALACHICOLA AIRPORT
ST GEORGE ISLAND
LITTLE ST GEORGE ISLAND
Indian Pass
Indian Lagoon
Cape San Blas Light
Apalachicola Light
Dog Island
Dog Island Light
Oyster Bay
Bulkhead Point
Bird Island
Bird Rookery
Cedar Island
Cedar Island Light
Cedar Island Reef
Cedar Island Reef Light
Cedar Island Reef Range Front
Cedar Island Reef Range Rear
Cedar Island Reef Range Light
Cedar Island Reef Light
Cedar Island Reef Light
Cedar Island Reef