This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

FISH TRAP AREAS

Boundary lines of fish trap areas are shown thus: ~ ~ ~ ~ ~ ~

Submerged piling may exist in these areas.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Hyannis, MA KEC-73 162.55 MHz

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 2 for important supplemental information.

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, and U.S. Coast Guard.

LOGARITHMIC SPEED SCALE

1 2 3 4 5 6 7 8 9 10 15 20 25 30 35 40 50 60

To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots.

Nautical Miles 1 ½ 0 1 2 3

Yards 1000 0 1000 2000 3000 4000 5000

SOUNDINGS IN FEET

13244

NOAA — NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION — DEPARTMENT OF COMMERCE — COAST SURVEY

UNITED STATES - EAST COAST

MASSACHUSETTS

EASTERN ENTRANCE

TO

NANTUCKET SOUND

Mercator Projection
Scale 1:40,000 at Lat. 41 30'
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Formerly C&GS 250, 1st Ed., Apr. 1893. C-1921-204. KAPP 2099

TIDAL INFORMATION

Place Name	(LAT./LONG.)	Height referred to datum of soundings (MLLW) Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
		feet	feet	feet	feet
Monomoy Point	(41°33'N/70°00'W)	4.0	3.8	0.1	-2.5
Great Point	(41°23'N/70°06'W)	3.3	3.2	0.1	-2.5

(12DH)

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical; Al alternating; Bl black; Bn beacon; C can; DIA diaphone; F fixed; Fl flashing; G green; Gp (interrupted) quick; Iso isophase; LT HO light-house; M nautical mile; m minutes; MICRO TR microwave tower; Mkr marker; Mo morse code; N nun; OBSC obscured; Oc occulting; Or orange; Q quick; R red; Ra Ref radar reflector; R Bn radiobeacon; R TR radio tower; Rot rotating; s seconds; SEC sector; St M statute miles; VQ very quick; W white; WHIS whistle; Y yellow.

Bottom characteristics:

Blds boulders; Co coral; gy gray; Oys oysters; so soft; bk broken; G gravel; h hard; Pk rock; Sh shells; cy clay; Grs grass; M mud; S sand; sy sticky; Subm submerged.

Miscellaneous:

AUTH authorized; ED existence doubtful; Obstn obstruction; PA position approximate; PD position doubtful; Repd reported; ⚓ Wreck, rock, obstruction, or shoal swept clear to the depth indicated; (2) Rocks that cover and uncover, with heights in feet above datum of soundings.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.394" northward and 1.970" eastward to agree with this chart.

NOTE B

AREA TO BE AVOIDED

All vessels carrying cargoes of oil or hazardous materials and all other vessels of more than 1,000 gross tons should avoid the area (MSC IMO XLIII/19).

★ 2002 ★ THE YEAR OF CLEAN WATER — Celebration of Recommitment

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 2. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 1st Coast Guard District in Boston, MA or at the Office of the District Engineer, Corps of Engineers in Concord, MA.

Refer to charted regulation section numbers.

ANCHORAGE AREAS

110.140 (see note A)

Limits and designations of anchorage areas are shown in magenta.

(I) (J) (K) GENERAL ANCHORAGES

COLREGS, 80.145 (see note A)

International Regulations for Preventing Collisions at Sea, 1972.

The entire area of this chart falls seaward of the COLREGS Demarcation Line.

Nautical Chart Catalog No. 1, Panel H


JOINS CHART 13229
CONTINUED ON CHART 13248
CONTINUED ON CHART 13237
JOINS CHART 13241
CONTINUED ON CHART 13237
65°
70°
55'
54'
50'
69°45'
35'
41°
30'
25'
SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.
SOURCE
B2 1970-1989 NOS Surveys partial bottom coverage
B3 1940-1969 NOS Surveys partial bottom coverage
B4 1900-1939 NOS Surveys partial bottom coverage
ANCHORAGE AREA (I)
ANCHORAGE AREA (J)
ANCHORAGE AREA (K)
MONOMOY I.
MONOMOY POINT
OLD TOWER (Ruined Lighthouse)
Monomoy Pt
Powder Horn
Ponds
Pond
ROGERS SHOAL
BEARSE SHOAL
Pollock Rip Channel
Broken part of Pollock Rip
POLLOCK RIP SHOAL
LOWER POLLOCK RIP
STONEHORSE SHOAL
LITTLE ROUND SHOAL
GREAT ROUND SHOAL
ORION SHOAL
CHANNEL
McBLAIR SHOAL
POLLOCK RIP
POLLOCK RIP CHANNEL
NANTUCKET SOUND
NANTUCKET HARBOR
Great Pt
Hazard Shoal
Fish Haven
Piling
NAUTICAL TWILIGHT
AREA TO BE AVOIDED (see note B)
MAGNETIC
VAR 16°00'W (2002)
ANNUAL DECREASE 7'
RW "POR" Mo (A) WHIS
RW "GRE" Mo (A) WHIS RACON (—)
Fl Y 6s "W" Priv PA
Fl Y 6s "E" Priv PA
Fl Y 6s "C" Priv PA
Y "B" Priv
Fl R 4s BELL
Fl G 4s
Fl G 2.5s BELL
Fl G 2.5s
Fl R 4s
Fl R 4s GONG
Fl R 2.5s
Fl G 2.5s
Fl G 4s
Fl R 4s
Fl G 4s
Fl R 4s
Fl G 4s
Fl R 4