UNITED STATES – EAST COAST

DELAWARE - PENNSYLVANIA - NEW JERSEY

DELAWARE RIVER

WILMINGTON TO PHILADELPHIA

Mercator Projection
Scale 1:40,000 at Lat. 39°51'
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

TIDAL INFORMATION

Name	(LAT./LONG)	Height referred to datum of soundings (MLLW) Mean Higher High Water feet	Mean High Water feet	Mean Low Water feet	Extreme Low Water feet
Wilmington, Christina River, DE	(39°44'N/75°33'W)	6.2	5.9	0.2	-6.0
Fairmount Water Works, PA	(39°58'N/75°11'W)	6.4	6.0	0.2	-6.0
Fairmount Bridge, PA	(39°58'N/75°11'W)	6.4	6.0	0.2	-6.0
Philadelphia, Municipal Pier 11, PA	(39°57'N/75°08'W)	6.5	6.3	0.2	-6.5
Billingsport, NJ	(39°51'N/75°14'W)	6.2	5.8	0.2	-6.5

(BSC)

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated)
AUTH Automatic
Bn daybeacon
B bell
Bn beacon
C can
DB diaphone
F fixed
Fl flashing
G green
Gp Fl (2) group flashing
Iso isophase
LT HO lighthouse
M nautical mile
m minutes
MICRO TR microwave tower
Mkr marker
Mo (A) Morse code
R TR radio tower
Ray radiating
s seconds
SEC sector
St M statute miles
VQ very quick
W white
Whis whistle
Y yellow

Bottom characteristics
Blds boulders
bk broken
Cy clay
Co coral
Gr gravel
Grs grass
gy gray
h hard
M mud
Oys oysters
Pk rock
S sand
so soft
Sh shells
sy sticky

Miscellaneous
AUTH authorized
ED evidence doubtful
Ex existence doubtful
Obstn obstruction
PA position approximate
PD position doubtful
Rep reported
Subm submerged

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography (from surveys of 1980-82) and topography by the National Ocean Service, Coast Survey with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

Nautical Miles 1

Yards -1000 0 1000 2000 3000 4000 5000

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.405" northward and 1.318" eastward to agree with this chart.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

NOTE B
CABLE AREAS

See larger scale chart 12313 for cable crossings in Reserve Basin, Big Timber Creek, and Back Channel.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.

During the winter months or when encountered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION

Only marine radiobeacons have been calibrated for surface use. Limitations on the use of certain other radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and Defense Mapping Agency Publication 117.

Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

(Accurate location) (Approximate location)

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service stations listed below provide continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Atlantic City, N.J.	KHB-38	162.40 MHz
Philadelphia, Pa.	KH-28	162.475 MHz

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 3 for important supplemental information.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION

BASCULE BRIDGE CLEARANCES

For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

CAUTION

Mariners are warned to stay clear of the protective riprap surrounding navigational light structures shown thus

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

DELAWARE RIVER CHANNEL DEPTHS

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - REPORT OF AUG 1986 AND SURVEYS TO JUL 1985

NAME OF CHANNEL	CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW) LEFT OUTSIDE QUARTER	LEFT MIDDLE HALF	RIGHT MIDDLE QUARTER	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	PROJECT DIMENSIONS WIDTH (FEET)	LENGTH (FEET)	DEPTH (FEET)
CHERRY ISLAND RANGE	39.8	39.8	41.5	40.8	9/85	800	4.00	40
BELLEVUE RANGE	37.5	41.1	41.5	40.8	9/85	800	3.50	40
MARCUS HOOK RANGE	39.2	41.2	39.1	39.4	9/85	800	4.00	40
EDGEMOOR RANGE	41.1	41.2	39.1	40.8	9/85	800	4.00	40
EDGESTONE RANGE	41.1	39.8	41.5	41.6	9/85	800	1.98	40
TINICUM RANGE	41.4	41.6	41.5	37.9	9/85	800	3.59	40
BILLINGSPORT RANGE	40.9	41.5	42.1	41.0	9/85	800	1.70	40
MIFFLIN RANGE	39.9	40.6	40.8	39.1	7/85	800	2.82	40
LIVELY POINT RANGE (EAST SIDE)	40.8	41.8	40.5	40.5	9/85	800	1.74	40
LIVELY POINT RANGE	40.8	41.8	40.5	40.5	9/85	800/400	1.98	40
HORSESHOE RANGE (AIR)	40.5	41.2	42.1	41.0	9/85	800	1.70	40
REACH W	40.0	42.7	42.9	44.5	9/85	400-500	1.17	40
REACH W TO DELAWARE-PENNSYLVANIA BRIDGE	39.9	37.1	40.5	40.5	9/85	400	2.66	40
REACH W TO PHILADELPHIA	40.0	41.2	41.7	41.7	9/85	400	3.00	40
PHILADELPHIA ALLEGHENY AVE.	41.7	41.7	41.7	41.7	9/85	400	3.00	40
FISHER POINT RANGE	41.4	39.5	42.1	42.1	9/85	400	3.70	40
FISHER CHANNEL	42.4	44.4	44.0	43.5	9/85	400	0.91	40
CRIM CHANNEL	42.7	42.7	43.8	43.8	9/85	400	0.74	40

A. SOUNDS ARE LOCATED APPROXIMATELY 40 FEET EAST OF THE CHANNEL CENTERLINE
B. APPROXIMATELY 39° 49'.4 N
NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried. Those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging or trawling.

Covered wells may be marked by lighted or unlighted buoys.

CHESTER CREEK

The controlling centerline depth at mean lower low water to the Third Street Bridge was 2 feet July 1957

RACCOON CREEK

The reported depths at mean lower low water were 4 feet for the entrance channel, thence 6½ feet reported on centerline to Bridgeport, thence 1½ feet reported on centerline to Swedesboro.

Mar. 1976 - July 1977

OLDMANS CREEK

The controlling centerline depths at mean lower low water were 1 foot to Pedricktown, thence 1.4 feet to Auburn.

Mar. 1957-1982

Extensive shoaling reported 1973-75.

LOCAL MAGNETIC DISTURBANCE

Differences of 2° to 5° from the normal variation have been observed astride the Delaware River Channel from Oldmans Point to the mouth of Oldmans Creek.

WOODBURY CREEK

The controlling centerline depth was 2 feet to first highway bridge, thence 3 feet to second highway bridge, thence less than 1 foot to Woodbury.

1965, 1981

BIG TIMBER AND MANTUA CREEKS

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO DEC 1976

CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)

NAME OF CHANNEL	DEPTH MLW (FEET)	WIDTH (FEET)	DATE OF SURVEY
BIG TIMBER CREEK			
CHANNEL ENTRANCE TO FIXED BRIDGE AT WESTVILLE	7.7	CENTERLINE	12-76
THENCE TO CLEMENTS BRIDGE	4.5	CENTERLINE	12-76
MANTUA CREEK			
CHANNEL ENTRANCE TO A POINT IN DEEPWATER, 75°14'W	16.5	CENTERLINE	3-76
THENCE TO PRIVATE LANDING	7.8	CENTERLINE	3-76
THENCE TO PURVEYS LANDING	3.3	CENTERLINE	3-76

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGING CONDITIONS SUBSEQUENT TO THE ABOVE

CHANNEL DEPTHS

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - REPORT OF MAY 1986 AND SURVEYS TO JUL 1985

NAME OF CHANNEL	CONTROLLING DEPTHS FROM SEAWARD IN FEET AT CHRISTINA RIVER DATUM LEFT OUTSIDE QUARTER	MIDDLE HALF Channel	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	PROJECT DIMENSIONS WIDTH (FEET)	LENGTH (FEET)	DEPTH (FEET)
ENTRANCE CHANNEL TO THE UPPER END OF THE TURNING BASIN	24.7	25.8	A to A 4	7/85	300	6.70	30
TRACK TO THE CEDRILL CANAL TURNING BASIN (OPPOSITE TERMINAL WHARF)	24.8	25.8	26.2	7/85	400	0.54	30
	26.1	26.2	26.4	3/85	300	0.54	30

A. SHOALING TO 10.5 FT EXISTS ON EDGE OF RUN IN VICINITY OF CHANNEL BUOY "F"
NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

ANCHORAGE AREAS

110.157 (see note A)

Limits and assigned numbers of anchorage areas are shown in magenta.

(6) (7) (8) (9) GENERAL ANCHORAGES

(10) NAVAL ANCHORAGE

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 3. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 5th Coast Guard District in Portsmouth, Virginia, or at the Office of the District Engineer, Corps of Engineers in Philadelphia, Pennsylvania.
Refer to charted regulation section numbers.

NOTE C

Depths refer to Schuylkill River Datum.

NOTE D

Depths refer to Christina River Datum.

Nautical Miles

Yards 1000 0 1000 2000 3000 4000 5000

LOGARITHMIC SPEED SCALE

2 3 4 5 6 7 8 9 10 15 20 25 30 40 50 60

To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.6 nautical miles run in 15 minutes, the speed is 18.4 knots

(CONTINUED ON CHART 12314)

(CONTINUED ON CHART 12313)

4th Ed., Sept. 1995
12312

CAUTION

This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910 - 3282.

Published at Washington, D.C.
U. S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FEET

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FEET	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102
METERS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17

(Delaware River, Wilmington to Philadelphia)
SOUNDINGS IN FEET SCALE 1:40,000

12312

LITIGATION FILE

45 (S) NC

12312A1 12312