NSN 7642014010369
ED. NO. 32
NGA REFERENCE NO. 12XHA12317

HEIGHTS
Heights in feet above Mean High Water.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 3 for important supplemental information.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers and U.S. Coast Guard.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Atlantic City, NJ	KHB-38	162.40 MHz
Lewes, DE	WXJ-94	162.55 MHz

PRINT-ON-DEMAND CHARTS
NOAA and its partner, OceanGrafix, offer this chart updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about Print-on-Demand charts or contact NOAA at 1-800-584-4683, http://NauticalCharts.gov, help@NauticalCharts.gov, or OceanGrafix at 1-877-56CHART, http://OceanGrafix.com, or help@OceanGrafix.com.

For Symbols and Abbreviations see Chart No. 1

COLREGS: International Regulations for Preventing Collisions at Sea, 1972.
Demarcation lines are shown thus: – – – –

COAST SURVEY

UNITED STATES – EAST COAST
NEW JERSEY
CAPE MAY HARBOR

Formerly C&GS 234, 1st Ed., Feb. 1931 G-1931-348 KAPP 679

Mercator Projection
Scale 1:10,000 at Lat. 38° 57'

North American Datum of 1983
(World Geodetic System of 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov.

TIDAL INFORMATION

Place Name (LAT/LONG)	Height referred to datum of soundings (MLLW) Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
	feet	feet	feet	feet
Cape May Harbor (38°57'N/74°53'W)	4.9	4.6	0.2	-3.0

(Dec 2001) Latest available information.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

SOUNDINGS IN FEET

12317

55' 74° 54' 53' CONTINUED ON CHART 12316 74° 52' 51'

CONTINUED ON CHART 12316

LOGARITHMIC SPEED SCALE
1 2 3 4 5 6 7 8 9 10 15 20 25 30 40 50 60
To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots.

SCALE 1:10,000
Nautical Miles ½ 0 ½
Yards 200 0 200 400 600 800 1000 1200
Meters 200 0 200 400 600 800 1000 1200

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 3. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 5th Coast Guard District in Portsmouth, Virginia or at the Office of the District Engineer, Corps of Engineers in Philadelphia, Pennsylvania.
Refer to charted regulation section numbers.

NOTE S
Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

RACING BUOYS
Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List.

NOTE B
Numerous lighted and unlighted buoys are not charted because they are frequently shifted in positions.

CAUTION
BASCULE BRIDGE CLEARANCES
For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

CAUTION
Mariners are warned to stay clear of the protective riprap surrounding navigational light structures shown thus: ⊙

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:
Pipeline Area — Cable Area
Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.403' northward and 1.380' eastward to agree with this chart.

SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE
A 1990 - 2002 NOS Surveys full bottom coverage
B2 1970 - 1989 NOS Surveys partial bottom coverage
B4 1900 - 1939 NOS Surveys partial bottom coverage

CAPE MAY CANAL
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - REPORT OF JUL 2000 AND SURVEYS TO JUN 2003

CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
FROM CANAL ENTRANCE TO CAPE ISLAND CREEK	11.5	11.2	11.1	4-03	100	0.35	12
FROM CAPE ISLAND CREEK TO INNER END OF FERRY BASIN	5.9	7.3	6.8	4-03,6-03	100	2.55	12
FROM INNER END OF FERRY BASIN TO DELAWARE BAY	10.5	11.0	9.8	6-03	100-150	0.44	12

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

CAPE MAY HARBOR
CAPE MAY
CAPE MAY INLET
SEWELL POINT
JARVIS SOUND
Cape May Canal
To Delaware Bay 3 miles
Mill Creek
Skunk Sound
Upper Thorofare
Ford Creek
Middle Thorofare
Lower Thorofare
Thorofare Island
Fish Wharf
Cedar Creek
Yacht Basin
Schellenger Creek
Schellenger Landing
Cape Island Creek
Cape Island Creek Range
Two Mile Beach
Pipeline Area
Cable Area
Foul Area
Numerous mooring buoys rap
Dump Site (dredged material) (see note S)
Depths from survey of 2002
DANGER AREA 334.100 (sunrise to sunset daily) (see note A)
COLREGS DEMARCATION LINE 80.501 (see note A)
BEACH AVENUE
PATTERSON AVENUE
Marsh
Piles
Pile
Piling
Subm pile
Subm piles
Pilng rap
Marine Railway
Ramp
Dock
Bkw
Rks PA
Obstn
Wk
Foul Area
Sy
S Sh
S
Y
C "A"
C "C"
TOWER
TANK
CG
LORAN TOWER
Fl R Lt 641ft
F 40ft
F 22ft (Day) Q 21ft (Night)
Fl R 4s 15ft 3M "4"
Fl (2+1) R 6s 15ft 3M "C"
Fl R 4s 12ft 3M "14"
Fl R 6s 15ft 4M "6"
Fl G 4s 15ft 4M "5"
Fl R 4s 15ft 4M "12"
G "3" Fl G 2.5s
R "2" Fl R 2.5s
R "2CM" Fl R 2.5s BELL
Fl G 4s 20ft 6M "5"
Fl R 4s 25ft 6M "4"
FIXED BRIDGE HOR CL 80 FT VERT CL 55 FT
FIXED BRIDGE HOR CL 38 FT VERT CL 4 FT
FIXED BRIDGE HOR CL 33 FT VERT CL 6 FT
FIXED BRIDGE HOR CL 80 FT VERT CL 61 FT
BASCULE BRIDGE HOR CL 50 FT VERT CL 53 FT
OVHD PWR CAB AUTH CL 75 FT
OVHD PWR CAB AUTH CL 34 FT
Cable and Pipeline Area
(See chart 12304)
(See note S)
(See note B)
MAGNETIC
VAR 12° 15'W(2004)
ANNUAL INCREASE 2'
VAR 14° 15'W(2004)

38° 56' 55' 74° 54' 53' 74° 52' 51' CONTINUED ON CHART 12214

32nd Ed., May / 04 ■ Corrected through NM May 8/04
Corrected through LNM Apr. 27/04
12317

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

FATHOMS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
FEET 6 12 18 24 30 36 42 48 54 60 66 72 78 84 90 96 102
METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Cape May Harbor
SOUNDINGS IN FEET - SCALE 1:10,000

12317

18"
25"