NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEAN SERVICE

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 7 for important supplemental information.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Charting and Geodetic Services with additional data from the Geological Survey and U.S. Coast Guard.

SOUNDINGS IN FEET

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Director, Charting and Geodetic Services (N/CG22), National Ocean Service, NOAA, Rockville, Maryland 20852.

For Symbols and Abbreviations see Chart No. 1

SOUNDINGS IN FEET

Soundings are referred to a lake level of 2048.15 feet above mean sea level

BRIDGES AND OVERHEAD CABLES

Vertical clearances are referred to a lake level of 2062.5 feet above mean sea level.

PROVISIONAL CHART

UNITED STATES

IDAHO

LAKE PEND OREILLE

Mercator Projection
Scale 1:50,000 at Lat. 48°08'
North American Datum of 1983
(World Geodetic System 1984)

Formerly C & GS 6170, 1st Ed., Sept. 1950

HEIGHTS in feet above mean sea level.

LAKE LEVEL

The normal winter lake level is 2051 feet above mean sea level which is 3 feet above the datum of the soundings.

The normal summer lake level is 2062.5 feet above mean sea level which is approximately 14 feet above the datum of the soundings.

The highest reported level of the lake is 2076 feet above mean sea level which is approximately 28 feet above the datum of the soundings.

Daily corrected lake level information can be obtained from the Albeni Falls Dam power house control room by phoning 208/437-3133.

CAUTION

During periods of rising lake level debris stranded on shore is floated and is present in large quantities in the lake. During this period, boats should proceed slowly and cautiously to avoid damage.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

Nautical Chart Catalog No. 2, Panel I

18554

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.296" southward and 3.682" westward to agree with this chart.

CAUTION

A high voltage overhead power cable follows the shoreline in Oden Bay. This cable intermittently crosses over open water.

LOCAL MAGNETIC DISTURBANCE

Differences of as much as 3° from the normal variation have been observed on shore approximately one nautical mile south of Whiskey Point.

LOGARITHMIC SPEED SCALE

To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots

Nautical Miles

Statute Miles

Yards

(Inner neatline 88.95 cm. N.S. x 59.55 cm. E.W.)

DMA STOCK NO. 18XHA18554

6th Ed., Sept. 1/90 ■

18554

CAUTION

This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner.

LITIGATION/COPY

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE

SOUNDINGS IN FEET

(Lake Pend Oreille)

SOUNDINGS IN FEET - SCALE 1:50,000

18554